CeyaKrete
construction chemicals & coatings

Manufactured by an ISO 9001 2015 Certified Company

TOUGH SEAL

SINGLE PART WATERPROOFING COATING

CeyaKrete ToughSeal is a one-part fiber-reinforced, cement based waterproofing solution. It is specially formulated for commercial and residential internal and external waterproofing applications. The fiber, reinforced composition of **CeyaKrete ToughSeal** combines amatrix binder within the membrane structure to provide extra strength to the membrane. **CeyaKrete ToughSeal** does not require the use of additional reinforcing matting.

TECHNICAL DATA

PROPERTIES: Gray Cement, Silica Sand, Water Repellent Acrylic Copolymer Emulsion, Anti Caking Agent

PACK SIZE: 25KG / 5KG / 1KG

COVERAGE: 6 – 7Sq.Ft / KG
(Depending on the surface condition)

APPLICATION THICKNESS: 0.5 - 1 MM (2 Coats)

MIXING RATIO: 01KG Tough Seal Powder: 310 – 350ml Water

COLOUR: Gray

DRYING TIME: 2 - 4 Hours

POT LIFE: 30 – 40 Minutes from the time of mixing

SHELF LIFE: Up to 12 months in unopened containers and stored in a cool dry elevated position



Member of CRI Group
ESTB 1950
Subsidiary of Ceylon Rubber Industries Ltd.

Ceyalac (Pvt) Ltd.
Ingiriya Road, Arukwatte, Padukka, Sri Lanka
+94 11 7222252
+94 11 2507770
info@ceyalac.com
www.ceyalac.com
Sales Hotline: 773 833 929